


## LUMINAIRE DATA

Picture	product name	color	Diffuser material	Beam angle	Base Type
	T8 LED	white	PC	210°	G13

## LIGHT SOURCE & DRIVER

Series	ZEUS Tube 0.6M Standard	ZEUS Tube 1.2M Standard	ZEUS Tube 1.2M high Efficiency	ZEUS Tube 1.5mm standard	ZEUS Tube 1.5M high Efficiency
System code	MY-T806I	MY-T812I	MY-T812L	MY-T815I	MY-T815L
LED Brand	Nichia/Seoul Semi/Epistar Mid Power SMD LED				
Input voltage(V AC)	100-240	100-240	100-240	180-240	180-240
CRI(Ra)	80	80	80	80	80
Color temperature	2700/3000/3500/4000/5000/5700/6500K				
Size(mm)(L*D)	588x26	1198x26	1198x26	1496x26	1496x26
Driver	Internal	Internal	Internal	Internal	Internal
Power Factor	> 0.9				
THD	<20%				
Power consumption	8W	14W	11W	20W	20W
System luminous flux	1050LM	2000LM	2000LM	2800LM	3400LM
LM/W	140LM/W	140LM/W	180LM/W	140LM/W	170LM/W
Efficiency Class	A++	A++	A++	A++	A++
Certification	CE PSE				
Power output range	3-12W	7-25W		18-25W	
System luminous flux range	500-1500LM	1100-4000LM		2500-4050LM	


\* standard Light source is Epistar, Nichia, Seoul Semi are options.

\* Lm/W be tested at 5000K CCT.

## ADDITIONAL DATA

	ZEUS Tube 0.6M Standard	ZEUS Tube 1.2M Standard	ZEUS Tube 1.2M high Efficiency	ZEUS Tube 1.5mm standard	ZEUS Tube 1.5M high Efficiency
Weight	110g	330g		352g	
Material	PC with Aluminium inside				
Ambient temperature range	-10 to 45				

## ADDITIONAL Accessoire

	LED Starter
Picture	
size	Φ20.8xH39mm
color	white